

ITEM		DIMENSIONS & TOLERANCES (mm)				
	SERIES	0.50	1.00	1.25	1.27	2.54
PITCH (P)		0.50±0.05	1.00±0.10	1.25±0.10	1.27±0.10	2.54±0.20
MARGIN (M)		0.50±0.08	1.00±0.10	1.25±0.10	1.27±0.10	2.54±0.20
POSITIONS (P)		4 ~ 99	4 ~ 196	3 ~ 79	3 ~ 77	2 ~ 38
WIDTH (W)		0.50(N+1)±-0.08	1.00(N+1)±-0.10	1.25(N+1)±-0.10	.27(N+1)±-0.10	2.54(N+1)±-0.20
SPAN (S)		0.50(N+1)±-0.08	1.00(N+1)±-0.10	1.25(N+1)±-0.10	.27(N+1)±-0.10	2.54(N+1)±-0.20
CONDUCTOR WIDTH (CW) X THICKNESS (CT)	SF	0.30X0.10	0.65X0.10	0.80X0.10	0.65X0.10	1.27X0.10
	EF	0.30X0.05	0.65X0.05	0.80X0.05	0.65X0.5	1.27X0.076
	UF	0.30X0.035	0.65X0.035	0.80X0.035	0.65X0.035	1.27X0.05
INSULATED THICKNESS (IT)	SF	(0.20 ~ 0.30)±0.03				
	EF	(0.15 ~ 0.20)±0.03				
	UF	(0.15 ~ 0.20)±0.03				
EXPOSURE (E1)		(2.0 ~ 6.0)±1.0				
STIFFENER (S1)		(4.0 ~ 20.0)±2.0				
EXPOSURE (E2)		(2.0 ~ 6.0)±1.0				
STIFFENER (S2)		(4.0 ~ 20.0)±2.0				
INSULATION LENGTH (IL)5		(20 ~ 100)±3				
		(101 ~ 300)±5				
		(301 ~ 600)±8				
TOTAL LENGTH (TL)		E1+E2+IL				
EXPOSURE THICKNESS (ET)		0.30±0.05				